Appl. No. : Nat'l Phase of PCT/NL2004/000007

Int'l Filing Date : January 8, 2004 Nat'l Phase Entry : July 11, 2005

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A Composition with fire retardant properties, comprising a high molecular organic material, and a fire retardant addition of aluminium hydroxide—and optionally further—fillers, characterized in that, wherein the high molecular organic material is linoleum cement.

- 2. (Currently amended) The composition Composition—according to claim 1, characterized in that, in addition to the further comprising other fillers, wherein the linoleum cement composition contains up to 38 wt. % of aluminium hydroxide.
- 3. (Currently amended) The composition Composition according to claim 1—or 2, wherein the composition contains-further comprises calcium carbonate as well, characterized in that, and the fire retardant composition contains 10-90 wt. % linoleum cement.
- 4. (<u>Currently amended</u>) The composition <u>Composition</u> according to claim 3, <u>characterized in that, wherein</u> in a linoleum cement composition about half of the calcium carbonate present for the manufacture of linoleum is replaced by aluminium hydroxide.
- 5. (Currently amended) The composition Composition according to claim 4, characterized in that, wherein the linoleum cement composition contains 5-25 wt. % of both calcium carbonate and as well as aluminium hydroxide, wherein the total weight percentage of both substances is 20-40 wt. %.
- 6. (Currently amended) The composition Composition according to claim 3, 4 or 5, eharacterized in that, wherein the calcium carbonate consists wholly or partly of limestone or another calcium carbonate containing mineral.
- 7. (Currently amended) The composition Composition—according to claim 1, wherein each of the foregoing claims, characterized in that, the fire retardant composition comprises a mainly cellulose containing filler., such as wood flour, cork flour, short natural fibres or rayon fibres.
- 8. (Currently amended) The composition Composition—according to claim 7, eharacterized in that, wherein the mainly of cellulose consisting containing filler is wood flour and/or cork flour.

Appl. No. : Nat'l Phase of PCT/NL2004/000007

Int'l Filing Date : January 8, 2004 Nat'l Phase Entry : July 11, 2005

9. <u>(Currently amended) The composition Composition</u> according to claim 8, eharacterized in that, wherein the linoleum cement composition contains 20-40 wt. % wood flour and/or cork flour.

10-14. (Canceled)

- 15. (New) The composition according to claim 7, wherein the cellulose containing filler comprises wood flour, cork flour, short natural fibres or rayon fibres.
- 16. (New) The composition according to claim 2, wherein the composition further comprises calcium carbonate and the fire retardant composition contains 10-90 wt. % linoleum cement.
- 17. (New) The composition according to claim 4 wherein the calcium carbonate consists wholly or partly of limestone or another calcium carbonate containing mineral.
- 18. (New) The composition according to claim 5 wherein the calcium carbonate consists wholly or partly of limestone or another calcium carbonate containing mineral.
- 19. (New) The composition according to claim 2, wherein the fire retardant composition comprises a mainly cellulose containing filler.
- 20. (New) The composition according to claim 3, wherein the fire retardant composition comprises a mainly cellulose containing filler.
- 21. (New) A fire retardant linoleum, comprising a high molecular organic material, and a fire retardant addition of aluminium hydroxide, wherein the high molecular organic material is linoleum cement.
- 22. (New) The fire retardant linoleum according to claim 21 in the form of a shaped object.
- 23. (New) The fire retardant linoleum according to claim 21 in the form of an object suitable for the covering of a floor, wall, ceiling, table or wallboard.
- 24. (New) The fire retardant linoleum according to claim 23, wherein the object is obtained by applying on a surface of linoleum elements manufactured from the fire retardant linoleum.